



Engineering Drawing (mm)

| | i. | |
|---|----------|----------|
| | 6 | |
| | Á | |
| | <u> </u> | |
| | | |
| | - Á | |
| | <u> </u> | |
| | ň | |
| 1 | Å. | |
| 1 | Ä | |
| 1 | Å | <u> </u> |
| 1 | Å | 1 |
| 1 | Å | 1 |
| 1 | 1 | |
| | | |







Specifications

| Model No. (Filter fan unit) | GF6626.230 | GF6626.115 |
|-----------------------------|---|------------|
| Rated operating voltage | 220 ~ 240V | 110 ~ 120V |
| Frequency | 50/60 Hz | 50/60 Hz |
| Air flow rate (Free blow) | 550/600 m³/h | |
| Air flow rate with filter | 1 x GF6626.300:380/410 m³/h | |
| Axial fan | Capacitor operated | |
| Max. rated current | 0.29/0.37A | 0.52/0.55A |
| Rated Power | 65/80W | |
| Noise level | 62/65 dB(A) | |
| Operating temperature range | -30°C ~ 70°C | |
| Model No. (Exit filter) | GF6626.300 | |
| Optional Fan Size | 1) 225x225x80mm | |
| Material | ABS; ABS plastic with UL 94V-0 as customized option | |
| Air flow direction | Air-in as default; air-out optional | |
| Protection Level | IP54 | |